

## Single Mode Coupler 980 or 1060nm (DL-SMC-T-UU-VV-W-X-Y-Z)

The Single Mode Coupler offers accurate coupling ratio from 50/50 to 1/99 and are available with very good uniformity in a wide wavelength range. It also has very low insertion loss, low polarization dependence and excellent environmental stability. It can be used to perform power splitting and monitoring functions in all kinds of optical communication systems.

### A. Specifications

Parameter	Value					Unit
Center Wavelength ( $\lambda_c$ )	980 or 1060					nm
Operating Wavelength	$\lambda_c \pm 10$					nm
Coupling Ratio	01/99	02/98	03/97	05/95	10/90	%
Max. Insertion Loss	21.9/0.25	18.5/0.3	16.5/0.35	14.5/0.45	11/0.7	dB
Coupling Ratio	20/80	30/70	40/60	50/50		%
Max. Insertion Loss	7.7/1.3	5.8/2.0	4.5/2.7	3.5/3.5		dB
Max. PDL (Tap/Through Port)	0.10					dB
Thermal Stability	$\leq 0.002$ over $-5^\circ\text{C}$ to $+70^\circ\text{C}$					dB/ $^\circ\text{C}$
Min. Return Loss	50					dB
Directivity 1 $\times$ 2	55					dB
2 $\times$ 2	60					dB
Max. Optical Power (Continuous Wave)	300					mW
Operating Temperature	$-5$ to $+70$					$^\circ\text{C}$
Storage Temperature	$-40$ to $+85$					$^\circ\text{C}$

\*IL is 0.5 dB higher, RL is 5 dB lower for each connector added.

### B. Ordering Information

#### DL-SMC-T-UU-VV-W-X-Y-Z

S: Package Dimensions	T: Configuration	UU: Wavelength	VV: Coupling Ratio	
1 - 250 $\mu\text{m}$ bare fiber, dia 3.0 $\times$ 40 mm	1 - 1 $\times$ 2	98 - 980 nm	01 - 01/99	20 - 20/80
2 - 900 $\mu\text{m}$ loose tube, dia 3.0 $\times$ 54 mm	2 - 2 $\times$ 2	06 - 1060 nm	02 - 02/98	30 - 30/70
3 - 3 mm cable, 90 $\times$ 16 $\times$ 9 mm		SS - Specify	03 - 03/97	40 - 40/60
			05 - 05/95	50 - 50/50
			10 - 10/90	SS - Specify

W: Connector Type	X: Fiber Type	Y: Fiber Length	Z: Fiber Option
1 - FC/UPC	B - 250 $\mu\text{m}$ bare fiber	1 - 1 m	H - HI 1060 Flex fiber
2 - FC/APC	L - 900 $\mu\text{m}$ loose tube	S - Specify	O - OFS 980 fiber
3 - SC/UPC	C - 3 mm cable		
4 - SC/APC	S - Specify		
N - None			
S - Specify			